


Elgen Superpoint Weld Pins



Product Data Sheet



Features

- Raised Head which allows better movement through the hopper
- Can be used in any Insulation Weld Pin Machine
- Rings in the nail head provide more consistent welds
- Superior strength (Average test is over 145 lbs of force)
- Beveled edge prevents tearing of the fiberglass liner
- Hardened washer provided added strength
- Meets SMACNA Standards
- (Refer to Chapter 7 figure 7-11 & 7-12)

Description

Elgen Superpoint Weld Pins are used for fastening Fiberglass Duct Liner to the inside of the Duct Wall.

Standard Construction

The pin is made from 10 GA Electroplated Galvanized Steel
 The washer is made from 28 gauge Full Hard Galvanized Steel

Packaging

Size (in)	Liner Thickness (in)	Density (lbs)	Bucket Qty	Weight (lbs)
1/2	1/2	All	6000	31
3/4	1	1-1/2	5000	33
1	1	3	4000	40
1-1/8	1-1/2	All	4000	34
1-1/4	1-1/2	All	4000	34
1-1/2	2	1-1/2 - 2	3500	35

Guarantee

All Elgen products are guaranteed by Elgen Manufacturing against defective material.

Elgen Manufacturing
 10 Railroad Ave, Closter NJ 07624
 Tel: 800.503.9805 :: Fax: 201.964.9030
 info@elgenmfg.com :: www.elgenmfg.com